


**seppi m.®**

**MULCHING EQUIPMENT SPECIALISTS**



**Quality by Design**

## **FLAIL MULCHERS**

### **MEDIUM DUTY**

**SML - SMWA REV CF - SMWA S**  
**SMWO - SMWA SLIM - SMWA K**  
**SMO - SMO REV CF - SMO FH**

20 - 95 HP





**Discover the  
Advantages of  
seppi m<sup>®</sup>**

## **INNOVATION**

- > over 70 years experience  
mulching equipment specialists since 1971
- > continuous research for new solutions and technologies
- > optimal material, with low wear

## **QUALITY**

- > every machine is tested before leaving the factory
- > use of the best components only
- > low wear

## **RELIABILITY**

- > high performance machines
- > close to customer sales and service network
- > fast and efficient customer care



For over 40 years, SEPPI flail mowers have been working to satisfy professionals in agriculture and greenspace maintenance. With a vast choice of options and accessories, every machine can be equipped according to specific professional needs.


*"I work with SEPPI mowers because they are tough and reliable machines, working fast and leaving a clean cut. Even after years of service, they don't seem to break. I also like the efficiency of these mowers, which helps me to save both time and costs."*

*Luis Romen, farmer and contractor Italy*


## SEPPI flail mowers up to 95 HP:

- › power from 20 to 95 HP
- › mulches grass, prunings and bushes up to 3, 5 and 7 cm [1.2, 2 and 2.8"] in diameter

## How to work with a SEPPI flail mower?



Open rear hood: to mulch grass with low power consumption



Closed rear hood: to smoothly mulch prunings and branches

## The SEPPI range of flail mowers

weight (kg/ lb)

1500	3310
1400	3090
1200	2650
1000	2200
800	1760
600	1320
400	880
200	440
0	

0	20	40	60	80	100	120	140	160
---	----	----	----	----	-----	-----	-----	-----

flail mowers - medium duty: 20-95 HP

flail mowers - heavy duty: 55-200 HP

WBS

OLS s

OLS

SMO

SMWA / SMWO

SML

power (HP)


## Powerful but light!

features	SML
mulches grass and prunings up to	3 cm [1.2"] Ø
working speed	3-5 km/h
ISO 3-point rear linkage	cat. 1 central fixed
gearbox with freewheel	540 rpm
input shaft	1 3/8" Z=6
number belts	3
support roller, adjustable in height	2,5 cm [1"]
front protection	metal flaps
rear protection	rubber flap
standard flails	SML


The SML flail mower is ideal for small HP tractors. Several different options are available for the machine, guaranteeing a perfect result, whatever the conditions.



manual parallel linkage  
55 cm [21.7"] side shift (option)  
- standard version  
central mounted.




rotor with SML flails (standard)  
(Y knives as an option)



model: SML

support roller and  
rear safety flap






The manual parallel linkage side shift, optional for the **SML** mower, allows to shift the mower up to 55 cm [21.7"] to the right.

As an option, the **SML** is also available with hydraulic parallel linkage side shift. The standard version is central fixed.

#### SML: manual parallel linkage side shift (option)



L = working width

d = 64 cm [25"]

D = 55 cm [22"]

options	SML	OPT
PTO drive shaft	O	008
rotor with Y knives on shackles	O	031
rotor with SMW flails	O	039
rotor with SML flails on shackles	O	342
manual parallel linkage side shift	O	206
hydraulic parallel linkage side shift	O	206 +046
chevrons for transportation on public roads	O	162

O: option

SML									
working width cm ["]	overall width cm ["]	depth cm ["]	height cm ["]	weight* kg [lb]	standard: SML flails #	option: SMW flails #	roller mm ["] Ø	kW** min-max	HP** min-max
105 [41]	125 [49]	90 [35]	95 [37]	265 [580]	18	9	133 [5.2]	15-29	20-40
125 [49]	145 [57]	90 [35]	95 [37]	290 [640]	24	12	133 [5.2]	15-29	20-40
155 [61]	175 [69]	90 [35]	95 [37]	330 [720]	27	15	133 [5.2]	15-29	30-40
175 [69]	195 [77]	90 [35]	95 [37]	350 [770]	33	18	133 [5.2]	15-29	30-40
200 [79]	220 [87]	90 [35]	95 [37]	380 [840]	39	21	133 [5.2]	15-29	35-40

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.

\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.



# The best choice for small tractors.


features	SMWA rev cf	SMWA s
mulches grass and prunings up to	5 cm [2"] Ø *	5 cm [2"] Ø
working speed	3-5 km/h	3-5 km/h
ISO 3-point linkage, reversible	cat. 1 & 2	up to 135 cm from 145 cm
side shift	17 cm [6.7"] manual	27 cm [10.6"] linear hydraulic
gearbox with freewheel and cross shaft	540 rpm	540 rpm
input shaft	1 3/8" Z=6	1 3/8" Z=6
number belts	up to 155 cm from 175 cm	3 4
support roller, adjustable in height	5 cm [2"]	5 cm [2"]
adjustable hood with rubber protection	S	S
front protection	metal flaps (OPT 181) or chains (OPT 025)	metal flaps (OPT 181) or chains (OPT 025)
standard rotor	SMW flails	SMW flails

S: standard

\* working width 225 cm: 3 cm [1,2"]

**Agriculture or greenspace maintenance?**
**All easy – with a strong flail mower mulching grass, prunings and bushes up to 5 cm [2"] in diameter.**

The SMWA is also available with an interface plate for skid steer loaders (see brochure „Hydr. Drive Mulchers“)



contoured casing prevents material hangup

gearbox with freewheel and cross shaft for front drive

model: SMWA s


hydraulic linear side shift on chrome plated parallel side shift (SMWA s)

counterknives inside the casing will give a perfect result when mulching

The **SMWA s** can be shifted to the right up to a maximum of 27 cm [10.6"].  
The side shift is linear and works even while the machine is mowing, with hydraulic control from the tractor seat.

The **SMWA rev cf** standard version has manual side shift with two position bolt-on hitch: central and 17 cm [6.7"] to the right.

#### SMWA s: linear side shift



L = working width  
D = 27 cm [10.6"]

options	SMWA rev cf	SMWA s	OPT
PTO drive shaft	O	O	008
rotor with Y knives	O	O	030
1000 rpm gearbox	O	O	018
gearbox with freewheel	O	O	066
additional 3-point linkage	O	O	096
rake hood with rakes	O	O	028
additional rubber front protection	O	O	006
XSC outrigger mower*	O	X	XSC
XSA cultivator*	O	X	XSA
XSP shoot remover*	O	X	XSP
XAN sweeper*	O	O	XAN
XID herbicide spraying system*	O	O	XID
chevrons for transportation on public roads	O	O	162

S: standard - O: option - X: not available  
\* for details refer to our brochure ACCESSORIES

	working width cm ["]	overall width cm ["]	depth cm ["]	height cm ["]	weight* kg [lb]		standard flails #	roller mm ["] Ø	kW** min-max	HP** min-max
					SMWA rev cf	SMWA s				
SMWA rev cf SMWA s	85 [34]	97 [38]	90 [35]	95 [37]	260 [570]	X	9	133 [5.2]	14-41	20-55
	95 [37]	107 [42]	90 [35]	95 [37]	290 [640]	X	9	133 [5.2]	14-41	20-55
	105 [41]	117 [46]	90 [35]	95 [37]	310 [680]	350 [780]	9	133 [5.2]	14-41	20-55
	115 [45]	127 [50]	90 [35]	95 [37]	320 [700]	370 [816]	12	133 [5.2]	16-41	21-55
	125 [49]	137 [54]	90 [35]	95 [37]	330 [730]	380 [838]	12	133 [5.2]	16-48	21-65
	135 [53]	147 [58]	90 [35]	95 [37]	360 [790]	410 [905]	12	133 [5.2]	19-48	26-65
	145 [57]	157 [62]	90 [35]	95 [37]	390 [860]	430 [948]	15	133 [5.2]	19-48	26-65
	155 [61]	167 [66]	90 [35]	95 [37]	420 [920]	440 [970]	15	133 [5.2]	22-48	30-65
	175 [69]	187 [74]	90 [35]	95 [37]	440 [970]	490 [1,080]	18	133 [5.2]	22-52	30-70
	200 [79]	212 [84]	90 [35]	95 [37]	470 [1,030]	520 [1,147]	21	133 [5.2]	26-52	35-70
	225 [89]	237 [93]	90 [35]	95 [37]	490 [1,080]	X	24	133 [5.2]	26-52	35-70

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.

\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.





# Ultra slim mulching mower!

features	SMWA slim
mulches grass and prunings up to	5 cm [2"] Ø
working speed	3-5 km/h
ISO 3-point linkage	cat. 1 & 2, reversible
side shift	linear hydraulic
gearbox with freewheel and through shaft	540 rpm
input shaft	1 3/8" Z=6
power belts	2+3
low belt protection	S
support roller, adjustable in height	5 cm [2"]
adjustable hood with rubber protection	S
front protection	metal flaps (OPT 181) or chains (OPT 025)
standard rotor	SMW flails

options	SMWA slim	OPT
PTO drive shaft	O	008
rotor with Y knives	O	030
1000 rpm gearbox	O	018
reinforced roller	O	066
additional 3-point linkage frame	O	096
rake hood with rakes	O	028
additional front rubber flap	O	006
XAN sweeper*	O	XAN
XID herbicide spraying system*	O	XID
chevrons	O	162

S: standard - O: option - X: not available  
\* for details refer to our brochure ACCESSORIES

The innovative drive concept and compact design make the **SMWA slim** highly manoeuvrable in tight situations. It allows the machine to mulch very close to the crop. Also it can work directly under the canopy without damaging fruit.

the power belts are very compact - this allows the machine to work very close to the crop

hydr. side shift

reversible linkage

low side frames work below the canopy without causing damage



SMWA slim									
working width cm ["]	overall width cm ["]	depth cm ["]	side height cm ["]	hitch height cm	weight* kg [lb]	standard flails #	roller mm ["] Ø	kW** min-max	HP** min-max
135 [53]	143 [56]	90 [35]	54 [21]	110 [43]	405 [893]	12	133 [5.2]	19-48	26-65
145 [57]	153 [60]	90 [35]	54 [21]	110 [43]	415 [915]	15	133 [5.2]	19-48	26-65
155 [61]	163 [64]	90 [35]	54 [21]	110 [43]	465 [1,025]	15	133 [5.2]	22-48	30-65
175 [69]	183 [72]	90 [35]	54 [21]	110 [43]	480 [1,058]	18	133 [5.2]	22-48	30-65
200 [79]	208 [82]	90 [35]	54 [21]	110 [43]	535 [1,180]	21	133 [5.2]	26-48	35-65
225 [89]	233 [92]	90 [35]	54 [21]	110 [43]	590 [1,300]	24	133 [5.2]	26-48	35-65

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.

\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.





# Power in a light package !

**new!**

features	SMWA k
mulches grass and prunings up to	5 cm [2"] Ø with forestry rotor 12 cm [5"]
working speed	0-10 km/h
ISO 3-point linkage	cat. 1 & 2, reverse drive
position of the linkage adjustable (2 slots)	by 17 cm [6.7"]
gearbox with manual inverter without freewheel	540 rpm
input shaft	1 3/8" Z=6
belts	4
support roller, adjustable in height	5 cm
adjustable hood with rubber protection	S
front protection	double chains
standard rotor	SMW flails

options	SMWA k	OPT
PTO drive shaft with freewheel	O	011
rotor with "SMW duo" flails *	O	326
rotor with Y knives *	O	030
forestry rotor with swinging hammers **	O	240
roller scraper	O	027
chevrons	O	162

S: standard - O: option





\* SMW duo, Y knife and swinging hammers work with both rotation directions

\*\* swinging hammers only available for working width 155 cm [61"] and 175 cm [69"]

Safe working thanks to the innovative

**STOPSAFE™ System:**

 The movement will stop when used incorrectly,  
minimizing thrown material.

direction of rotation & thrown material	
recommended	non recommended
	
	

**Compact mulcher for professional & universal use  
with specific characteristics**

With a double skin casing made of wear resistant steel,  
the **SMWA k** is a perfect mulcher for exacting conditions.  
The lightweight construction allows work on sloping ground.  
With a manual inverter the mulching result can be optimized.  
Depending on the direction of the rotor shaft it mulches  
low or high grass and brush.



SMWA k							
working width cm ["]	overall width cm ["]	depth cm ["]	height cm ["]	weight* kg [lb]	standard flails #	kW** min-max	HP** min-max
155 [61]	167 [66]	90 [35]	105 [41]	425 [940]	15	26 - 52	35 - 70
175 [69]	187 [74]	90 [35]	105 [41]	480 [1060]	18	26 - 52	35 - 70
200 [79]	212 [84]	90 [35]	105 [41]	540 [1190]	21	26 - 52	35 - 70
225 [89]	237 [93]	90 [35]	105 [41]	610 [1350]	24	26 - 52	35 - 70

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.

\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.



# When mulching becomes your profession.


features	SMWO		SMO	
mulches grass and prunings up to	5 cm [2"] Ø		7 cm [2.8"] Ø	
working speed	3-5 km/h		3-5 km/h	
ISO 3-point linkage	1. u. 2. Kat.		up to 225cm from 250 cm	1. u. 2. Kat. 2. Kat.
parallel linkage side shift	S		S	
gearbox with freewheel and cross shaft	540 U/min		up to 200cm from 225 cm	540 U/min 1000 U/min
input shaft	1 3/8" Z=6		1 3/8" Z=6	
number of belts	up to 155cm from 175 cm	3 4	up to 200cm from 225 cm	4 5
support roller, adjustable in height	5 cm		5 cm	
adjustable hood with rubber protection	S		S	
front protection	metal flaps (OPT 181) or chains (OPT 025)		metal flaps (OPT 181) or chains (OPT 025)	
standard rotor with flails	SMW		up to 200cm from 225 cm	SMO SMW

S: standard


The models SMWO and SMO are distinguished by an extraordinarily wide side shift to the right.

The parallel linkage system allows the machines to work under the trees and close to the crop leaving a much cleaner result.

All other features are those of a perfect mulcher meeting the needs of the best farmers.



## parallel linkage side shift



L = working width  
d = 69 cm [27"]  
D = 73 cm [28.7"]

The standard versions are equipped with manual side shift, hydraulic side shift is optional. Total side shift is 73 cm [28.7"].

options	SMWO	SMO	OPT
PTO drive shaft	O	O	008
rotor with Y knives	O	O	030
hydraulic side shift	O	O	046
540 rpm gearbox	S	O	019
1000 rpm gearbox	O	O	018
rake hood with rakes	O	O	028
additional front rubber flap	O	O	006
rubber gauge wheels	X	O	035
XSC outrigger mower*	O	O	XSC
XSA cultivator*	O	O	XSA
XSP shoot remover*	O	O	XSP
XAN sweeper*	O	O	XAN
XTR conveyer belt*	X	O	XTR
XID herbicide spraying system*	O	O	XID
chevrons for transportation on public roads	O	O	162

S: standard - O: option - X: not available  
\* for details refer to our brochure ACCESSORIES

	working width cm ["]	overall width cm ["]	depth cm ["]	height cm ["]	weight* kg [lb]	standard flails #	roller mm ["] Ø	kW** min-max	HP** min-max
SMWO	125 [49]	137 [54]	120 [47]	95 [37]	350 [774]	12	133 [5.2]	16-48	21-65
	135 [53]	147 [58]	120 [47]	95 [37]	400 [878]	12	133 [5.2]	19-48	26-65
	145 [57]	157 [62]	120 [47]	95 [37]	420 [926]	15	133 [5.2]	19-48	26-65
	155 [61]	167 [66]	120 [47]	95 [37]	430 [948]	15	133 [5.2]	22-48	30-65
	175 [69]	187 [74]	120 [47]	95 [37]	480 [1,050]	18	152 [5.2]	22-52	30-70
	200 [79]	212 [83]	120 [47]	95 [37]	500 [1,100]	21	152 [5.2]	26-52	35-70
SMO	125 [49]	140 [55]	120 [47]	120 [47]	460 [1,010]	12	133 [5.2]	29-63	40-85
	150 [59]	165 [65]	120 [47]	120 [47]	490 [1,080]	15	133 [5.2]	29-63	40-85
	175 [69]	190 [75]	120 [47]	120 [47]	540 [1,190]	18	133 [5.2]	29-63	40-85
	200 [79]	215 [85]	120 [47]	120 [47]	590 [1,300]	21	133 [5.2]	35-63	48-85
	225 [89]	240 [95]	120 [47]	120 [47]	650 [1,430]	24	152 [5.2]	35-70	48-95
	250 [98]	265 [104]	120 [47]	120 [47]	710 [1,560]	24	152 [5.2]	41-70	55-95

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.  
\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.





# When mulching becomes your profession.

features	SMO rev cf		SMO fh
mulches grass and prunings up to	7 cm [2,8"] Ø *		7 cm [2,8"] Ø *
working speed	3-7 km/h		3-7 km/h
reversible ISO 3-point linkage	cat. 2 , central fixed		cat.1 & 2
side shift	X		linear hydraulic
gearbox with freewheel and through shaft	1000 rpm		1000 rpm
input shaft	1 3/8" Z=6		1 3/8" Z=6
number belts	up to 200 cm	4	4
	from 225 cm	5	5
support roller, adjustable in height	5 cm		5 cm
adjustable hood with rubber flap	S		S
front protection	metal flaps (OPT 181) or chains (OPT 025)		metal flaps (OPT 181) or chains (OPT 025)
standard rotor / flails	up to 200 cm	SMO	SMO
	from 225 cm	SMW	SMW


S: standard - X: not available

\* working width 275 cm: 5 cm [2"]

Road sides, meadows, pastures –  
the SMO satisfies the needs of  
professionals in the most varied situations  
with an ever clean cut.

The new version of the SMO fh is  
characterized by an innovative,  
pyramid-shaped 3-point linkage,  
suitable for front and rear attachment.  
The top link connection may be reversed very  
easily, so allowing front or rear mount to be  
achieved without any heavy lifting.



This linkage provides high stability and  
also the side shift is now very stressable.



rotor with  
SMO flails /  
SMW flails

**new  
version !**


model: SMO fh



metal flaps or, as an  
alternative, chain protection

compact side shift -  
weight is close to the tractor  
(model: SMO fh)

## SMO fh: side shift



L = working width

L = 150-175: D = 17 cm [7"]

L = 200-275: D = 28 cm [11"]

The **SMO fh** may be shifted to the left and to the right up to a maximum of 17 cm [6.7"] (for working widths up to 175 cm) or up to a maximum of 28 cm [11"] (for working widths from 200 cm). The side shift is linear and works even while the machine is working, with hydraulic control from the tractor seat. The **SMO rev cf** has no side shift.

options	SMO rev cf	SMO fh	OPT
PTO drive shaft	O	O	008
rotor with Y knives	O	O	030
540 rpm gearbox	O	O	019
gearbox with automatic inverter and double freewheel for reversible tractors	O	O	066
additional 3-point-linkage frame	O	S	096
rake hood with rakes	O	X	028
additional front rubber flap	O	O	006
rubber gauge wheels	O	O	035
XSC outrigger mower*	O	X	XSC
XSA cultivator*	O	X	XSA
XSP shoot remover*	O	X	XSP
XAN sweeper*	O	O	XAN
XID herbicide spraying system*	O	O	XID
chevrons for transportation on public roads	O	O	162

S: standard - O: option - X: not available  
\* for details refer to our brochure ACCESSORIES

	working width cm ["]	overall width cm ["]	depth cm ["]	height cm ["]	weight* kg [lb]		standard flails #	roller mm ["] Ø	kW** min-max	HP** min-max
					SMO rev cf	SMO fh				
SMO rev cf SMO fh	150 [59]	165 [65]	120 [47]	120 [47]	470 [1,030]	640 [1,410]	15	133 [5.2]	29-63	40-85
	175 [69]	190 [75]	120 [47]	120 [47]	540 [1,190]	710 [1,570]	18	133 [5.2]	29-63	40-85
	200 [79]	215 [85]	120 [47]	120 [47]	580 [1,280]	760 [1,680]	21	133 [5.2]	35-63	48-85
	225 [89]	240 [95]	120 [47]	120 [47]	630 [1,380]	820 [1,810]	21	152 [5.2]	35-70	48-95
	250 [98]	265 [104]	120 [47]	120 [47]	690 [1,520]	900 [1,990]	24	152 [5.2]	41-70	55-95
	275 [108]	280 [110]	120 [47]	120 [47]	740 [1,630]	990 [2,180]	27	152 [5.2]	41-70	55-95

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.

\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.





# Maintenance in the Orchards & Vineyards and Equipment for Organic Farming

To keep the orchards clean, SEPPI M. offers a classic spraying system as well as several mechanical attachments for organic farming. The accessories are connected to the mulcher with a quick coupling system. Some of the attachments can be added to an independent carrier.

Please find an overview of our products below. For further details refer to our brochure ACCESSORIES.



The **outrigger XSC** is specialized for inter-row mowing. The double XSC outrigger also adapts to row widths. This makes mowing much faster and more efficient.



The **cultivator XSA** supports organic agriculture. A mechanical process cuts the roots of weeds and brings them to the surface.



The brushes of the **shoot remover XSP** clean the trunk and remove shoot, suckers and straw mechanically – without chemicals.



With the **sweeper XAN** you may collect leaves and prunings from row sides and bring them into an ideal position for mulching: in front of the mulching mower.



The **conveyor belt XTR** deposits grass to the right of the mulcher. This inhibits the growth of the grass and allows to reduce the use of chemicals.



The **herbicide spraying system XID** may be mounted to many SEPPI mowers. High-precision nozzles come with adjustable spraying direction.



## ROTORS AND FLAILS



SML ROTOR

standard on **SML**



SML flail - flail on shackle - Y knives on shackle



SMW and SMO ROTOR

standard on **SMWA, SMWO** and **SMO**  
option on **SML**



SMW flail, SMO flail, SMW duo flail  
3-Y knives SMW, SMO



FORESTRY ROTOR

option on **SMWA k**



swinging hammer

All contents reserved.  
Specifications are subject to change without prior notice.



## The Advantage of High Quality

### Mulching Equipment Pioneers

Founded in 1939 by Max Seppi, SEPPi M. is now one of the foremost manufacturer in its sector - not only in Europe, but worldwide. A pioneer like no other, SEPPi has been manufacturing mulching equipment for more than 40 years. SEPPi's mission is "To improve the professional's work through innovative and efficient solutions".

The many years of experience, together with the tireless research for more advanced technologies and more resistant materials result in the premium quality of the SEPPi equipment with tough machines that are reliable even under extreme working conditions.

The biggest gratification over the past 70 years has been our satisfied customers, who have benefitted from long and efficient work with the SEPPi equipment – a continuous motivation to keep on focusing on high quality!  
The family-based character of the company today being led by the third generation, stands for fair and responsible business relationships.

**Discover the many advantages of owning SEPPi equipment!**



### AGRICULTURAL, FORESTRY AND INDUSTRIAL MOWERS

SEPPi M. S.p.A. - Zona Artigianale 1 - I-39052 Caldaro (Bolzano) Italy  
Tel. +39 0471 963550 - Fax +39 0471 962547 - [sales@seppi.com](mailto:sales@seppi.com) - [www.seppi.com](http://www.seppi.com)

AUTHORIZED DEALER

Ask our team for further information!